

Door Care Guide

For a longer lasting kitchen, follow these guidelines.

DO NOT USE abrasive or aggressive cleaners, bleach or other hypochlorite (chlorine) based cleaners, multipurpose-cleaners, dilutes, acetone, alcohol, solvent or similar products on the door as this will damage the surface.

Dust with a soft cloth following the grain pattern of the wood. For product cleaning use a 5% soap, 95% water (liquid soap) solution, wiping with a damp (not wet) cloth and finally drying with soft clean cloth.

It is advisable to use a damp (not wet) cloth to remove fingerprints and marks, followed at once with a clean and dry soft cloth. Cooking splashes should be wiped up immediately using a damp cloth.

Newly plastered rooms should be left to environmentally stabilise before storage and installation of doors.

Please note, unfinished timber doors have different care needs depending on the type of finish applied, eg paint, stain, wax etc., and you should contact your supplier of surfacing finish for care guidance.

If you have any further questions regarding looking after your new kitchen then do please get in touch and we will try help.

Gloss Surface. Any High Gloss Laser Edged doors and panels come with a protective film.

Once this film is removed it will initiate the curing process. It takes approximately 72 hours for the surface to be completely cured. Furthermore the removal of the protective film generates static electricity that attracts abrasive material to the surface.

It is in this period of time that the gloss material is most vulnerable to micro-scratching damage if an incorrect cleaning process is used.

For more information call our helpful team on 01934 813201